

IQ-IJ427/428

TruColor Display FR

Characteristics

- Compatible with (eco) solvent and UV-curable inks.
- For brilliant colors ink settings must be optimized according to ink printer and software instructions.
- From experience the optimum temperatur of the heaters should not exceed 40°C / 104°F.
- **Attention:** To ensure an easy removal of the paper backing adjust the heaters of the printer to a max. of 35°C / 95°F.

Applications

- Flags
- Window draperies
- Textile wall hangings
- Display booths
- Shop/Show decorations
- Indoor signs
- Displays
- Curtains

Technical Data

Material	100% knitted polyester
Withness CIE 158 2°/D50	L*a*b* 88/4,8/-18,1
Weight/Thickness	196 g/m ² ; 0,38 mm
With backing	271 g/m ² ; 0,45 mm
Print side	Coated side out
Reverse side	Removable backing
Flame retardant certificates	Germany: DIN-4102-B1 California: CA 1237
Green*	yes
Recyclable	yes
Biodegradable	no

Customs

Dutycode: 5903 9010

Description: Textile fabrics impregnated, coated, covered or laminated with plastics: of man-made fibers

***Definitions:**

Green: Produced according to the environmental management system EN ISO 14001 and the quality management standard EN ISO 9001. Moreover the production is validated in regard to the EU-wide regulation about ecological audits and the certified manufacturing process avoids atmospheric and environmental pollution.

The textiles contain no heavy metals, PVC resins, phthalates or fungicides.

IQ-IJ427/428

is suitable to be printed with (eco) solvent and UV curable ink.

Please test the product to be sure that the final result will satisfy your expectations.

Please consider our General Guidelines. Available at www.3P-inktextiles.com.